## Smarty 2X P 1.2



Specific energy consumption (SEC) cold	[ kWh/m²a ]	-75.3
Specific energy consumption (SEC) average	[ kWh/m²a ]	-37.4
Specific energy consumption (SEC) warm	[ kWh/m²a ]	-13
Declared typology		bidirectional
Type of drive installed (fan)		Variable
Type of heat recovery system		recuperative
Thermal efficiency of heat recovery	[%]	86.3
Maximum flow rate	[ m³/h ]	218
Electric power input of the fan drive at maximum flow rate	[W]	104
Sound power level (Lwa)	[ dB(A) ]	49
Reference flow	[ m <sup>3</sup> /s ]	0.042
Reference pressure difference	[ Pa ]	50
SPI	[ W/(m³/h) ]	0.33
Control factor and control typology		0.85
Declared maximum internal leakage rates	[%]	1.2
Declared maximum external leakage rates	[%]	1.2
Possition and description of visual filter warning for RVU's		Timer
AEC average	[ kWh ]	344
AEC cold	[ kWh ]	881
AEC warm	[ kWh ]	299
AHS Average	[ kWh/a ]	4530
AHS Cold	[ kWh/a ]	8861
AHS Warm	[ kWh/a ]	2048
ErP Compliance		2018
Internet address for disassembly instructions		www.salda.lt

