

Specific energy consumption (SEC) cold	[ kWh/m <sup>2</sup> a ]	-77.2
Specific energy consumption (SEC) average	[ kWh/m <sup>2</sup> a ]	-39.1
Specific energy consumption (SEC) warm	[ kWh/m <sup>2</sup> a ]	-14.7
Declared typology		bidirectional
Type of drive installed (fan)		Variable
Type of heat recovery system		recuperative
Thermal efficiency of heat recovery	[ % ]	86.9
Maximum flow rate	[ m <sup>3</sup> /h ]	394
Electric power input of the fan drive at maximum flow rate	[ W ]	170
Sound power level (Lwa)	[ dB(A) ]	50
Reference flow	[ m <sup>3</sup> /s ]	0.077
Reference pressure difference	[ Pa ]	50
SPI	[ W/(m <sup>3</sup> /h) ]	0.26
Control factor and control typology		0.85
Declared maximum internal leakage rates	[ % ]	1.2
Declared maximum external leakage rates	[ % ]	1.2
Possition and description of visual filter warning for RVU's		Timer
AEC average	[ kWh ]	280
AEC cold	[ kWh ]	817
AEC warm	[ kWh ]	235
AHS Average	[ kWh/a ]	4546
AHS Cold	[ kWh/a ]	8893
AHS Warm	[ kWh/a ]	2056
ErP Compliance		2018
Internet address for disassembly instructions		<a href="http://www.salda.lt">www.salda.lt</a>

